

PowerBoost: Unprecedented Coating Performance

Thanks to Gema's PowerBoost® technology your OptiSelect® ProX GM06 manual gun and OptiGun® GA04 automatic gun can now deliver **110 kV high voltage!**

This outstanding feature gives you **extra power** to increase transfer efficiency, charge more powder and finish your coating job quicker. PowerBoost gives the gun always sufficient power reserve.

All this without compromising the safety of your operators and of your line, thanks to Gema's advanced **protection technology**.



Higher Productivity,
Faster Coating Speed

Super Safe
Operation

Maximum
Coating Performance

PowerBoost: How Does it Work?

The high-performance technology is based on the combination of three essential components (*see an example on the right*):

- Electrostatic Control
with **advanced software** for charging process and compliance with safety regulation
- Powder Gun
with **high performance cascade**
- PowerBoost Nozzle
has special design for more **efficient charging**




OptiSpray All-in-One



OptiGun GA04



PowerBoost Nozzle NF40



PowerBoost Nozzles

PowerBoost Nozzle characteristics:

- Cloud soft could
wide brush spray pattern $>55^\circ$
- Material non stick high quality materials
(PTFE / ETFE / PP)
- Application ideal for large parts and fast
coating



*Flat jet nozzle NF40
For manual and automatic coating*



*Flat jet nozzle NF50
For robot coating*



PowerBoost: Activation


- Direct switch on gun (*toggle between PowerBoost and previous program settings*)
- On OptiStar ProX (*without CAN-Bus connection*) by selecting spray voltage above 100kV
- E-App by typing spray voltage above 100kV
- MagicControl MAX (CM50) selecting spray voltage above 100 kV

Manual gun OptiSelect GM06	Automatic gun OptiGun GA04
X	
X	X
X	
	X



PowerBoost: Super Safe Operation

- Thanks to the **PowerBoost** mode, your gun can now deliver **110 kV / 110 μ A**
- The **intelligent** technology **monitors** the charging process and **ensures safety** in every coating condition for your operators and your coating line.



EN 50050-2:2013, EN 50177:2009/A1:2012